# **Core Video Metadata Profile**

Version 1.0

14 March 1997

## **Contents**

| 1. INTRODUCTION                                | J |
|--|---|
| 1.1 Background                                 | 1 |
| 1.2 Document Purpose                           |   |
| 1.3 Document Scope                             |   |
| 2. Applicable Documents                        |   |
| 3. Core Video Metadata Set                     |   |
| 3.1 Relationship to USIGS Metadata             |   |
| 3.2 Table of Core Video Metadata Elements      |   |
| 3.3 Elements Mapped to the NIMA Metadata Model |   |
| 4. Acronyms and Abbreviations                  |   |
|  |   |

#### 1. INTRODUCTION

#### 1.1 Background

The Central Imagery Office (CIO)-chaired Video Working Group (VWG) created the Video Metadata Group (VMG) to identify metadata for efficient storage and access of video data. As a result of increased interest in video imagery in the Department of Defense and Intelligence (DoD/IC) communities, VMG membership is open to academia, commercial industry, and government.

The VWG tasked the VMG to develop and coordinate a community-wide common set of video metadata, compliant with existing metadata standards, primarily the United States Imagery System (USIS) Standards Profile for Imagery Archives (SPIA). In cases where no metadata elements exist, new ones will be created, coordinated with the community, and added to the standards via the appropriate request for change (RFC) process. In October 1996 the CIO was integrated into the National Imagery and Mapping Agency with several other imagery and geospatial oriented organizations. The enterprise architecture providing the services associated with NIMA business processes is now the United States Imagery and Geospatial Information System (USIGS). There will be a transition period to update CIO and DMA and related organizations' documentation to NIMA documents.

Quantity, format, and precision boundaries will be placed on the video metadata collective core set based on the need for community-wide commonality, migration strategies, current commercial video equipment technical constraints, and standards. As the intelligence and commercial communities migrate from analog to digital video, it is necessary to ensure the flexibility to extend the video metadata set for simplified data handling in the digital environment.

Video metadata development will occur on different scales. Today's operational needs include video archiving, exploitation, and dissemination; mapping and co-registration; and community-wide interoperability. Mid-term community requirements will identify the need for increased quality, accuracy, and additional video tools. Long term requirements must address seamless insertion into the imagery and geospatial chain, including tasking, collection, exploitation, reporting, product generation, and engineering studies and evaluations.

#### 1.2 Document Purpose

This standard is intended to define the core set of metadata that must be present, when feasible, in analog and digital video signals. Supporting current "analog video" with a coordinated set of metadata (for near term implementation) was a significant factor in the choosing of specific data elements. However, this standard also provides a stable foundation for metadata supporting digital video both in the near and far term. Discussion of specific technical issues is beyond the scope of this document; refer to the VWG Technical Report, *USIS Video Imagery Technical Information*, for further details.

#### 1.3 Document Scope

This document will apply to all programs that collect, exploit, store, or otherwise handle video. Video teleconferencing (VTC) applications are specifically excluded. It provides guidance to developing programs and will prove useful during migration of existing programs.

#### 2. APPLICABLE DOCUMENTS

The documents listed below are either referenced standards or resources containing additional information.

- United States Imagery and Geospatial Information System (USIGS) Standards Profile for Imagery Access (SPIA), NSPIA, 14 March 1997
- National Imagery Transmission Format for the National Imagery Transmission Format Standard, MIL-STD-2500A, Version 2.0, 12 October 1994 and Notice 1, 7 February 1997
- National Imagery Transmission Format Standard Profile for Imagery Archive Extensions (NITFS PIAE), Version 2.0, 25 April 1996
- Airborne Synthetic Aperture Radar (SAR) Support Data Extensions (SDE) for the National Imagery Transmission Format (NITF), Version 2.0, of the National Imagery Transmission Format Standards, RASG-9606-001, 20 May 1996
- Video Working Group USIS Video Imagery Technical Information Technical Report, VWG/TR-001-96, Version 1.0, 22 November 1996United States Imagery System Directive 2-1.1, Exploitation and Reporting Structure (EARS-1.1): Electronic Reporting, CIO-3P-005-95, 9 February 1995, Change Notice 02
- The Digital Geographic Information Exchange Standard (DIGEST), Edition 1.2, January 1994
- DoD Geospatial Data Standardization Project Report, Volume 3, Geospatial Metadata, 16 September 1996

#### 3. CORE VIDEO METADATA SET

#### 3.1 Relationship to USIGS Metadata

The VMG primarily used the existing SPIA as stated in section 1.1 and will coordinate addition of appropriate elements as shown in table 3-1. Table 3-2 depicts the elements which already existed in the SPIA version 1.0. Table 3-3 and Table 3-4 represent those elements approved by the Imagery Standards Management Committee/Geospatial Standards Management Committee (ISMC/GSMC) on 14 March 1997 to be added to the SPIA. The Core Video Metadata Profile appears in the USIGS SPIA, dated 14 March 1997, as appendix III.

As part of the larger data standardization effort many of the elements correlate with data elements named and defined in the NIMA Metadata Model (*DoD Geospatial Data Standardization Project Report*, Volume 3, Geospatial Metadata). Those mappings are shown in table 3-5. As the NIMA Metadata Model is further coordinated and the Data Standardization is implemented, element titles may be modified with current descriptions and domain values remaining valid.

#### 3.2 Table of Core Video Metadata Elements

The following table presents the data elements in alphabetical order. Attention must be given various elements which are connected, functionally equivalent, or extend the future processing options of products. Notes # 1, 2, 3, are applicable to specific elements as labeled in this table and repeated in section 3.3 which categorizes the elements.

Note 1: Sensor position may be expressed by several functionally equivalent element sets. SENSOR X DIMENSION, SENSOR Y DIMENSION, and SENSOR Z DIMENSION (ECEF Cartesian coordinates) or SENSOR ALTITUDE, SENSOR LATITUDE, and SENSOR LONGITUDE (decimal degrees) or SENSOR ALTITUDE and SENSOR LATLONG (degrees, minutes, seconds).

Note 2: FOCAL LENGTH and FIELD OF VIEW have some functionally equivalent characteristics. FOCAL LENGTH or FIELD OF VIEW, SENSOR ROLL ANGLE, ANGLE TO NORTH, and sensor depression angle (the inverse of OBLIQUITY ANGLE)) are used to reconstruct a trapezoid defining the area covered by the video frame.

Note 3: The geographical centerpoint of a video frame may be defined by FRAME CENTER LATITUDE and FRAME CENTER LONGITUDE (decimal degrees) or FRAME CENTER LATLONG (degrees, minutes, seconds).

Table 3-1

| In<br>Existing<br>SPIA? | Element Name             | Short Name       | Char<br>Type | Length | <b>Description/Comments</b>  | Repeating? | Domain  |
|-------------------------|--------------------------|------------------|--------------|--------|--|------------|---|
| Y                       | ANGLE TO<br>NORTH        | ANGLETO<br>NORTH | N            | 3      | Angle in degrees from the first row of the image to true north (See Note 2)                                      | Y          | 000 to 359  |
| Y                       | CLASSIFICATIO<br>N       | CLASS            | A            | 1      | Indicates the classification level of the product  | Y          | T Top Secret S Secret C Confidential R Restricted U Unclassified                      |
| Y                       | DATUM                    | DATUM            | A            | 3      | Identifies the map datum used to derive the target coordinates (UTM or GEO)                                      | N          | Domain valuea as listed in the DDDS for data element Horizontal-Reference-Datum-Code. |
| N<br>add to<br>SPIA     | FIELD OF VIEW            | FOV              | N            | 3      | Sensor field of view in<br>degrees (See Note 2)  | Y          | 0 to 180 degrees  |
| N<br>add to<br>SPIA     | FOCAL LENGTH             | FOCLNGTH         | N            | 5      | Focal length of the lens at<br>time of collection<br>measured in millimeters<br>(See Note 2)                     | Y          | nnnnnnnnnnnnnn (fixed point ) (TBR)<br>NNNN.N in millimeters for video                |
| N<br>add to<br>SPIA     | FRAME CENTER<br>LATITUDE | FRCNTLAT         | N            | 9      | Specifies the video frame<br>center point geographic<br>location in decimal degrees<br>of latitude. (See Note 3) | Y          | ± dd.ddddd - where "+" is northern<br>hemisphere and "-" is southern hemishere        |

| In<br>Existing<br>SPIA? | Element Name                    | Short Name | Char<br>Type | Length | Description/Comments  | Repeating? | Domain  |
|-------------------------|---------------------------------|------------|--------------|--------|---|------------|---|
| N<br>add to<br>SPIA     | FRAME CENTER<br>LATLONG         | FRCNTLTLG  | A/N          | 15     | Specifies a video frame center point geographic location in latitude and longitude (See Note 3).          | Y          | dd degrees latitude ddd degrees longitude mm minutes ss seconds X N for north S for south Y E for east W for west   |
| N<br>add to<br>SPIA     | FRAME CENTER<br>LONGITUDE       | FRCNTLON   | N            | 10     | Specifies the video frame center point geographic location in decimal degrees of longitude. (See Note 3)  | Y          | ± ddd.ddddd - where "+" is eastern<br>hemisphere and "-" is western hemishere   |
| N<br>add to<br>SPIA     | FRAME<br>POSITIONAL<br>ACCURACY | FRPSNACC   | N            | 4      | Accuracy of FRAME<br>CENTER coordinates as a<br>Circular Error Probable<br>(CEP) (50%)                    | у          | NNNN in meters  |
| Y<br>update<br>SPIA     | IMAGE<br>CATEGORY               | ICAT       | A            | 8      | Identifies the specific category of imagery (often revealing the nature of the collector or intended use) | Y          | As defined in NITF v2.0, plus:  SL Side-Looking Radar  TI Thermal Infrared  FL Forward Looking Infrared  RD Radar  EO Electro-optical  OP Optical  HR High Resolution Radar  HS Hyperspectral  VDEO Electro-optical Video  VDOP Optical Video  VDTI Thermal Infrared Video  VDFL Forward Looking Infrared Video  CP Color Frame Photography  BP Black/White Frame Photography |

| In<br>Existing<br>SPIA? | Element Name                  | Short Name | Char<br>Type | Length | <b>Description/Comments</b>   | Repeating? | Domain   |
|-------------------------|-------------------------------|------------|--------------|--------|---|------------|--|
| Y                       | IMAGE<br>COORDINATE<br>SYSTEM | ICORDS     | A            | 1      | Indicates the geo-<br>referenced coordinate<br>system for the image   | Y          | U UTM D Decimal Degrees (WGS 84) G Geodetic C Geocentric N None                |
| Y                       | MISSION<br>NUMBER             | MSNNUM     | A/N          | 1-7    | Identifies the mission<br>number assigned to the<br>mission   | N          | As defined by EARS Vol 1.1   |
| Y                       | OBLIQUITY<br>ANGLE            | OBLANGLE   | N            | 5      | Obliquity angle of image expressed in degrees (See Note 2)  | Y          | 00.00 to 90.00<br>The inverse of sensor depression angle                       |
| N<br>add to<br>SPIA     | PRODUCT<br>START TIME         | PRODSTRT   | A/N          | 14     | Video product start date<br>and time in UTC. Accurate<br>to within 1 second of the<br>acquisition of the first line<br>of the first image | N          | YYYYMMDDHHMMSS  yyyy year mm month dd day hh hour mm minute ss second          |
| Y                       | PROJECT ID<br>CODE            | PROJID     | A            | 2      | Identifies collection platform project identifier code  | Y          | As defined by EARS Vol 1.1   |
| N<br>add to<br>SPIA     | SENSOR<br>ALTITUDE            | SENSALT    | N            | 5      | Altitude of sensor as<br>measured from Mean Sea<br>Level (MSL) expressed in<br>feet (See Note 1)  | Y          | NNNN   |
| N<br>add to<br>SPIA     | SENSOR<br>LATITUDE            | SENSLAT    | N            | 9      | Specifies a sensor's<br>geographic location in<br>decimal degrees of latitude<br>(See Note 1)   | Y          | ± dd.ddddd - where "+" is northern<br>hemisphere and "-" is southern hemishere |

| In<br>Existing<br>SPIA? | Element Name          | Short Name | Char<br>Type | Length | <b>Description/Comments</b>   | Repeating? | Domain  |
|-------------------------|-----------------------|------------|--------------|--------|---|------------|---|
| N<br>add to<br>SPIA     | SENSOR<br>LATLON      | SENSLTLG   | A/N          | 15     | Specifies a sensor's geographic location in degrees, minutes, seconds of latitude and longitude (See Note 1)                        | Y          | dd degrees latitude ddd degrees longitude mm minutes ss seconds X N for north S for south Y E for east W for west |
| N<br>add to<br>SPIA     | SENSOR<br>LONGITUDE   | SENSLON    | N            | 10     | Specifies a sensor's geographic location in decimal degrees of longitude (See Note 1)   | Y          | ± ddd.ddddd - where "+" is eastern<br>hemisphere and "-" is western hemishere                                     |
| N<br>add to<br>SPIA     | SENSOR MODEL          | SENSMODEL  | A/N          | 4      | Identifies the name of the sensor model used in capturing the image   | Y          | TBD   |
| Y                       | SENSOR NAME           | SENSNAME   | A/N          | 18     | Identifies the name of the sensor used in capturing the image   | Y          | TBD   |
| N<br>add to<br>SPIA     | SENSOR ROLL<br>ANGLE  | SENSRANG   | N            | 4      | Specifies the roll angle of the sensor (See Note 2).  | Y          | ± 180 in degrees  |
| N<br>add to<br>SPIA     | SENSOR X<br>DIMENSION | SENSXDMN   | N            | 13     | Specifies the sensor<br>location along the x axis in<br>Earth Centered, Earth<br>Fixed (ECEF) Cartesian<br>coordinates (See Note 1) | Y          | ± NNNNNNNNNN in meters  |
| N<br>add to<br>SPIA     | SENSOR Y<br>DIMENSION | SENSYDMN   | N            | 13     | Specifies the sensor<br>location along the y axis in<br>Earth Centered, Earth<br>Fixed (ECEF) Cartesian<br>coordinates (See Note 1) | Y          | ± NNNNNNNN.NNN in meters  |

| In<br>Existing<br>SPIA? | Element Name          | Short Name | Char<br>Type | Length | <b>Description/Comments</b>   | Repeating? | Domain  |
|-------------------------|-----------------------|------------|--------------|--------|---|------------|---|
| N<br>add to<br>SPIA     | SENSOR Z<br>DIMENSION | SENSZDMN   | N            | 13     | Specifies the sensor<br>location along the z axis in<br>Earth Centered, Earth<br>Fixed (ECEF) Cartesian<br>coordinates (See Note 1) | Y          | ± NNNNNNNNN in meters   |
| N<br>add to<br>SPIA     | SLANT RANGE           | SLRNGE     | N            | 5      | Distance from the sensor to<br>the image center point on<br>ground expressed in feet  | Y          | NNNN  |
| N<br>add to<br>SPIA     | VIDEO TIME<br>STAMP   | VTMSTP     | A/N          | 8      | Indicates the time the video was captured and the related frame number.   | Y          | Per ANSI/SMPTE 12M-1995 HHMMSSFF  hh hour mm minute ss second ff unique field associated down to frame or specific instance of hhmmss |

The data elements below existed in SPIA version 1.0.

Table 3-2

| Angle to North          |
|-------------------------|
| Classification          |
| Datum                   |
| Image Category          |
| Image Coordinate System |
| Mission Number          |
| Obliquity Angle         |
| Project ID Code         |
| Sensor Name             |

Data elements below are various ways to depict locations. Two locations needed for video are for the sensor and the center of the video frame. The IMAGE COORDINATE SYSTEM (ICOORDS) data element indicates which coordinate system is being used. The method of representing geospatial locations by coordinates is in a To Be Determined (TBD001) status pending establishment of a final standard by the Imagery Standards Management Committee/Geospatial Standards Management Committee (ISMC/GSMC). Until that determination has been made, this core set will allow coordinates to be expressed in either decimal degrees; degrees, minutes, and seconds; or ECEF cartesian. The preferred representation is decimal degrees.

Table 3-3

| Frame Center Latitude     |
|---------------------------|
| Frame Center Longitude    |
| Frame Center LatLong      |
| Frame Positional Accuracy |
| Sensor Latitude           |
| Sensor Longitude          |
| Sensor LatLong            |
| Sensor Altitude           |
| Sensor X Dimension        |
| Sensor Y Dimension        |
| Sensor Z Dimension        |

The following elements were added for video unique needs or information required to perform further processing activities.

Table 3-4

| Focal Length       |
|--------------------|
| Field of View      |
| Product Start Time |
| Sensor Model       |
| Sensor Roll Angle  |
| Slant Range        |
| Video Time Stamp   |

#### 3.3 Elements Mapped to the NIMA Metadata Model

DoD Directive 8320.1 directed its agencies to standardize data elements for use in DoD systems and established the Defense Data Dictionary System (DDDS) as the central repository. NIMA is responsible for elements pertaining to Mapping, Charting, Geodesy, and Imagery data. The NIMA model is an essential tool in this standardization process. The following table depicts the elements having a close if not exact relationship in description and function. Core Video Metadata elements with no related affiliate will be designated for inclusion in the model.

Table 3-5

| Core Video Metadata       | NIMA Metadata Model                  |
|---------------------------|--------------------------------------|
| Angle to North            | IMAGE True North Angle               |
| Classification            | SECURITY CLASSIFICATION Code         |
| Datum                     | HORIZONTAL-REFERENCE-DATUM Code      |
| Image Category            | SENSOR Category Code                 |
| Image Coordinate System   | HORIZONTAL-COORDINATE-SYSTEM Code    |
| Mission Number            |                                      |
| Obliquity Angle           | IMAGE Obliquity Angle                |
| Project ID Code           |                                      |
| Sensor Name               |                                      |
| Frame Center Latitude     |                                      |
| Frame Center Longitude    |                                      |
| Frame Center LatLong      |                                      |
| Frame Positional Accuracy |                                      |
| Sensor Latitude           | IMAGE-EXPLOITATION-SUPPORT-DATA      |
|                           | Position Latitude                    |
| Sensor Longitude          | IMAGE-EXPLOITATION-SUPPORT-DATA      |
|                           | Position Longitude                   |
| Sensor LatLong            |                                      |
| Sensor Altitude           |                                      |
| Sensor X Dimension        | Sensor X Dimension                   |
| Sensor Y Dimension        | Sensor Y Dimension                   |
| Sensor Z Dimension        | Sensor Z Dimension                   |
| Focal Length              | IMAGE Focal Length Dimension         |
| Field of View             |                                      |
| Product Start Time        | IMAGE-EXPLOITATION-SUPPORT-DATA Time |
| Sensor Model              |                                      |
| Sensor Roll Angle         | IMAGE-EXPLOITATION-SUPPORT-DATA      |
|                           | Attitude Omega Angle                 |
| Slant Range               |                                      |
| Video Time Stamp          |                                      |

### 4. ACRONYMS AND ABBREVIATIONS

CIO Central Imagery Office

DARO Defense Airborne Reconnaissance Office

DIGEST Digital Geographic Information Exchange Standard

DoD Department of Defense

EARS Exploitation and Reporting Structure

ECEF Earth Centered Earth Fixed ESD Exploitation Support Data GMT Greenwich Mean Time

GSMC Geospatial Standards Management Committee
ISMC Imagery Standards Management Committee

MSL Mean Sea Level

NIMA National Imagery and Mapping Agency NITF National Imagery Transmission Format

NITFS National Imagery Transmission Format Standard

PIAE Profile for Imagery Archive Extensions

RFC Request for Change SAR Synthetic Aperture Radar SDE Support Data Extensions

SPIA Standard Profile for Imagery Access

TEM Technical Exchange Meeting USIS United States Imagery System

USIGS United States Imagery and Geospatial Information System

UTM Universal Transverse Mercator

VMG Video Metadata Group VTC Video teleconferencing VWG Video Working Group